



## RIDE IP54 R

220-240V AC/DC · CRI >90 · Binning SDCM 3

SYS 10W (nicht dimmbar/not dimmable)

**W2** = 820lm    **W3** = 890lm    **W4** = 930lm

577-014011023XX0 **W2** L: 606mm  
 577-014011029XX0 **W3** L: 606mm  
 577-014011024XX0 **W4** L: 606mm

SYS 19W

**W2** = 1650lm    **W3** = 1790lm    **W4** = 1860lm

577-014031023XXY **W2** L: 1163mm  
 577-014031029XXY **W3** L: 1163mm  
 577-014031024XXY **W4** L: 1163mm

SYS 48W

**W2** = 4130lm    **W3** = 4490lm    **W4** = 4670lm

577-014051023XXY **W2** L: 2846mm  
 577-014051029XXY **W3** L: 2846mm  
 577-014051024XXY **W4** L: 2846mm

SYS 15W

**W2** = 1230lm    **W3** = 1340lm    **W4** = 1400lm

577-014021023XXY **W2** L: 883mm  
 577-014021029XXY **W3** L: 883mm  
 577-014021024XXY **W4** L: 883mm

SYS 24W

**W2** = 2060lm    **W3** = 2240lm    **W4** = 2330lm

577-014041023XXY **W2** L: 1443mm  
 577-014041029XXY **W3** L: 1443mm  
 577-014041024XXY **W4** L: 1443mm

SYS 71W

**W2** = 6190lm    **W3** = 6730lm    **W4** = 7000lm

577-014061023XXY **W2** L: 4246mm  
 577-014061029XXY **W3** L: 4246mm  
 577-014061024XXY **W4** L: 4246mm

LED Lichtprofil aus stranggepresstem Aluminium  
 Oberfläche eloxiert oder weiß pulverbeschichtet  
 Geeignet für den Einbau in Zwischendecken von 1-20mm  
 Flache PMMA Abdeckung

Extruded aluminium LED profile  
 Anodised or white powder coated finish  
 For false ceiling 1-20mm thickness  
 Flat PMMA diffuser

Profilo in alluminio pressofuso a LED  
 Finitura anodizzata o verniciatura a polveri bianca  
 Per cartongesso spessore 1-20mm  
 Diffusore PMMA piatto

Profil en aluminium pressé de LED  
 Finis anodisé ou vernissage à poudres blanc  
 Pour placoplâtre de 1-20mm  
 Diffuseur PMMA plat

Die Schutzart IP54 wird nur bei Deckenmontage der  
 Leuchte gewährleistet  
 IP54 protection applies for ceiling installation only

**W2** = LED 2700K  
**W3** = LED 3000K  
**W4** = LED 4000K

**A++** - **A**

IP 54

### ARTIKELNUMMER ERGÄNZEN / COMPLETE CODE

**XX** = FARBE/COLOUR

**Y** = DIMMBAR/DIMMABLE

**W** white = 05  
**S** black = 06  
**AE** aluminium anodized = 08

**S** switchable = 0  
**D** DALI dimm = d

