



## RIDE IP54 SD

220-240V AC/DC · CRI >90 · Binning SDCM 3

### SYS 10W (nicht dimmbar/not dimmable)

1:  $\overline{W2}$  = 820lm     $\overline{W3}$  = 890lm     $\overline{W4}$  = 930lm  
 2:  $\overline{W2}$  = 920lm     $\overline{W3}$  = 1010lm     $\overline{W4}$  = 1050lm

577-01301C023XX0     $\overline{W2}$     L: 578mm  
 577-01301C029XX0     $\overline{W3}$     L: 578mm  
 577-01301C024XX0     $\overline{W4}$     L: 578mm

### SYS 15W

1:  $\overline{W2}$  = 1230lm     $\overline{W3}$  = 1340lm     $\overline{W4}$  = 1400lm  
 2:  $\overline{W2}$  = 1390lm     $\overline{W3}$  = 1510lm     $\overline{W4}$  = 1510lm

577-01302C023XXY     $\overline{W2}$     L: 851mm  
 577-01302C029XXY     $\overline{W3}$     L: 851mm  
 577-01302C024XXY     $\overline{W4}$     L: 851mm

### SYS 19W

1:  $\overline{W2}$  = 1650lm     $\overline{W3}$  = 1790lm     $\overline{W4}$  = 1860lm  
 2:  $\overline{W2}$  = 1850lm     $\overline{W3}$  = 2020lm     $\overline{W4}$  = 2100lm

577-01303C023XXY     $\overline{W2}$     L: 1137mm  
 577-01303C029XXY     $\overline{W3}$     L: 1137mm  
 577-01303C024XXY     $\overline{W4}$     L: 1137mm

### SYS 24W

1:  $\overline{W2}$  = 2060lm     $\overline{W3}$  = 2240lm     $\overline{W4}$  = 2330lm  
 2:  $\overline{W2}$  = 2320lm     $\overline{W3}$  = 2520lm     $\overline{W4}$  = 2620lm

577-01304C023XXY     $\overline{W2}$     L: 1418mm  
 577-01304C029XXY     $\overline{W3}$     L: 1418mm  
 577-01304C024XXY     $\overline{W4}$     L: 1418mm

LED Lichtprofil aus stranggepresstem Aluminium  
 Oberfläche eloxiert, weiß oder schwarz pulverbeschichtet  
 Nur für Deckenmontage geeignet  
 Flache oder vorspringende kubische Abdeckung

Extruded aluminium LED profile  
 Anodised, white or black powder coated finish  
 For ceiling mount only  
 Flat or cubic diffuser

Profil in alluminio pressofuso a LED  
 Finitura anodizzata, verniciatura a polveri bianca o nero  
 Solo per installazione a soffitto  
 Diffusore piatto o cubico

Profil en aluminium pressé de LED  
 Finis anodisé, vernissage à poudres blanc ou noir  
 Seulement pour montage au plafond  
 Diffuseur plat ou cubique

Die Schutzart IP54 wird nur bei Deckenmontage der  
 Leuchte gewährleistet  
 IP54 protection applies for ceiling installation only

$\overline{W2}$  = LED 2700K  
 $\overline{W3}$  = LED 3000K  
 $\overline{W4}$  = LED 4000K

A++ - A

IP 54

### SYS 48W

1:  $\overline{W2}$  = 4130lm     $\overline{W3}$  = 4490lm     $\overline{W4}$  = 4670lm  
 2:  $\overline{W2}$  = 4640lm     $\overline{W3}$  = 5050lm     $\overline{W4}$  = 5250lm

577-01305C023XXY     $\overline{W2}$     L: 2817mm  
 577-01305C029XXY     $\overline{W3}$     L: 2817mm  
 577-01305C024XXY     $\overline{W4}$     L: 2817mm

### SYS 71W

1:  $\overline{W2}$  = 6190lm     $\overline{W3}$  = 6730lm     $\overline{W4}$  = 7000lm  
 2:  $\overline{W2}$  = 6970lm     $\overline{W3}$  = 7570lm     $\overline{W4}$  = 7870lm

577-01306C023XXY     $\overline{W2}$     L: 4217mm  
 577-01306C029XXY     $\overline{W3}$     L: 4217mm  
 577-01306C024XXY     $\overline{W4}$     L: 4217mm

## ARTIKELNUMMER ERGÄNZEN / COMPLETE CODE

C = ABDECKUNG/COVER

XX = FARBE/COLOUR

Y = DIMMBAR/DIMMABLE

PMMA opal diffuser flat = 1

$\overline{W}$  white = 05

$\overline{S}$  switchable = 0

PMMA opal diffuser cubic = 2

$\overline{S}$  black = 06

$\overline{D}$  DALI dimm = d

$\overline{AE}$  aluminium anodized = 08

