



LED Ringleuchte aus stranggepresstem Aluminium
 Oberfläche eloxiert, weiß oder schwarz pulverbeschichtet
 LED Konverter im Leuchtenprofil integriert
 Inkl. flache PMMA-Abdeckung

LED ring luminaire, extruded aluminium
 Anodised surface, white or black powder-coated
 Built-in LED converter in profile
 Incl. flat PMMA diffuser

Lampada in alluminio estruso a forma di anello
 Superficie anodizzata o verniciata a polvere in bianco o nero
 Converter LED integrato nel profilo
 Incl. copertura piatta in PMMA

Lampe en forme d'anneau en aluminium extrudé
 Finition anodisée ou laquée blanc ou noir
 Convertiseur intégré dans le profil
 Incl. couvercle plat en PMMA

W2 = LED 2700K
W3 = LED 3000K
W4 = LED 4000K

A++ - **A**

IP 20  

RIDE RING PD

220-240V AC/DC · CRI >90 · Binning SDCM 3 · DALI dimm.

| SYS 38W / Ø 750mm | lm W2 | lm W3 | lm W4 |
|-------------------------|--------------|--------------|--------------|
| 675-20101102WXXd | 3300 | 3590 | 3730 |

| SYS 76W / Ø 1450mm | lm W2 | lm W3 | lm W4 |
|-------------------------|--------------|--------------|--------------|
| 675-20201102WXXd | 6610 | 7180 | 7470 |

ARTIKELNUMMER ERGÄNZEN / COMPLETE CODE

W = LICHTFARBE/LIGHT COLOUR

XX = FARBE/COLOUR

W2 LED 2700K = 3
W3 LED 3000K = 9
W4 LED 4000K = 4

W white = 05
S black = 06
AE aluminium anodized = 08

