



Einbaudownlight aus Aluminium
Pulverbeschichtet in weiß oder schwarz
Vakuumbelagter Alureflektor in 3 Ausstrahlwinkeln
Strahlerelement 355° drehbar und 30° schwenkbar
Konverter separat ordern

Recessed downlight in aluminium
white or black powder-coated
Vacuum deposited reflector in 3 beam angles
Spotlight 355° swiveling and 30° tilting
please order converter separately

downlight in alluminio ad incasso
verniciato in bianco o nero opaco
Ottica in alluminio in 3 fasci di emissione
Proiettore orientabile 355° orizzontale e 30° verticale
converter da ordinare separatamente

Downlight encastré en aluminium
Finition laquée blanc ou noir
Réflecteurs aluminium, 3 faisceaux disponibles
Projecteur tournant à 355°, pivotant à 30°
convertisseur à commander séparément

LED 3500K auf Anfrage / on request

Universal-Betoneinbaugeschäule: siehe Seite 498-499
Universal concrete housing: see page 498-499

A++ - A

IP20

RINE ROUND R

Binning SDCM 3 exkl. Konverter / excl. converter

Power feed

Order converter not dimm.
Order converter Dali dimm.

685-0010002WWXX 22°
685-0010005WWXX 36°
685-0010008WWXX 45°

350mA - 12W			500mA - 17W			700mA - 25W		
24-127530			24-127532			24-127534		
24-127490			24-127490			24-127490		
lm	W2	W3	lm	W2	W3	lm	W2	W3
1230	1280	1370	1690	1760	1880	2240	2330	2490
1230	1280	1370	1690	1760	1880	2240	2330	2490
1230	1280	1370	1690	1760	1880	2240	2330	2490

ARTIKELNUMMER ERGÄNZEN / COMPLETE CODE

WW = LICHTFARBE/LIGHT COLOUR

XX = FARBE/COLOUR

W2	LED 2700K = 43	PREMIUM CRI >90
W3	LED 3000K = 49	PREMIUM CRI >90
W4	LED 4000K = 24	CRI >90

W	white = 05
S	black = 06

LED CONVERTER RINE ROUND

24-127530	W	schaltbar/switchable	for 350mA	L 130 x B 42 x H 30mm
24-127532	W	schaltbar/switchable	for 500mA	L 130 x B 42 x H 30mm
24-127534	W	schaltbar/switchable	for 700mA	L 130 x B 42 x H 30mm
24-127490	W	DALI dimm.	for 350 - 700mA	L 130 x B 42 x H 30mm

