



Stromschienenleuchte aus stranggepresstem Aluprofil
Oberfläche weiß oder schwarz pulverbeschichtet
LED Konverter im Leuchtenprofil integriert

Track luminaire, extruded aluminium profile
black or white powder-coated surface
with LED converter in profile

Lampada in alluminio estruso per binario
verniciato a polvere in bianco o nero
Converter LED integrato nel profilo estruso

Luminaire sur rail en aluminium extrudé
laquée blanc ou noir
Convertisseur intégré dans le profil

W2 = LED 2700K
W3 = LED 3000K
W4 = LED 4000K

VOLARE Schienensystem: Seite 246-249
VOLARE track system: page 246-249



IP20

V-LINE VOLARE

220 - 240V AC · CRI >90 · Binning SDCM 3

SYS 11W	lm W2	lm W3	lm W4
694-11002102 W050 W	730	790	820
694-11002102 W060 S	670	730	760



V-LINE VOLARE ZIGBEE DIMM

220 - 240V AC · CRI >90 · Binning SDCM 3

SYS 9W	lm W2	lm W3	lm W4
694-11001102 W05z W	580	630	660
694-11001102 W06z S	540	580	610



ARTIKELNUMMER ERGÄNZEN / COMPLETE CODE

W = LICHTFARBE/LIGHT COLOUR

W2 LED 2700K = 3
W3 LED 3000K = 9
W4 LED 4000K = 4

